Schematic of TX-86 Transmitter.





CARBON MICROPHONE CONNECTIONS

1. Remove 12AX7 from socket.
2. Cut wire from chassis to pin 8 and ground pin 7 with it.
3. Add a wire from pin 8 to J1 terminal with .001 condenser (microphone).
4. Put 12AX7 tube and shield back.

AMECO — American Electronics Co. — 178 HERRICKS ROAD MINEOLA, L. I., N. Y. — AMECO

TX-86 PARTS LIST

Tubes

	12V	6V
V1 -	12BY7	12BY7
V2 -	6BQ5	6BQ5
V3 -	6883	6146
V4 -	12AX7	12AX7
V5 -	12AQ5	6AQ5

Inductances

L 1 - 2.5 mh RF choke
L 2 - 6 turns #16
L 3 - Special-Osc. plate coil
L 4 - 5 turns #22 Parasitic suppressor
L 5 - 1. mh RF choke
L 6 - 2.5 mh RF choke
L 7 - Special - Final grid coil
L 8 - 5 turns #22 Parasitic suppressor
L 9 - 3 turns #14 Parasitic suppressor
L10 - Special RF choke
L11 - 4-1/2 turns #14. 6 meter PI-net coil
L12 - Special 10 thru 80 meter PI-net coil
L13 - 2.5 mh RF choke

Connectors

J1 - Microphone and Key jack #JK33
J2 - SO-239 Coaxial jack
P1 - Amphenol 86CP6

Capacitors

C 1 - 22 mmfd. disc ceramic NPO
C 2 - 100 mmfd tubular ceramic N750
C 3 - .001 mfd. disc ceramic
C 4 - .001 mfd. disc ceramic
C 5 - 100 mmfd. variable (OSC PLATE)
C 6 - 100 mmfd. tubular ceramic
C 7 - .001 mfd. disc ceramic
C 8 - .001 mfd. disc ceramic
C 9 - .001 mfd. disc ceramic
C10 - 100 mmfd. tubular ceramic
C11 - .001 mfd. disc ceramic
C12 - 80 mmfd. variable (FINAL GRID)
C13 - 470 mmfd. ceramic feed-thru
C14 - 10 mfd. electrolytic 50V
C15 - .001 mfd. disc ceramic
C16 - .001 mfd. disc ceramic
C17 - .001 mfd. disc ceramic
C18 - .002 mfd. disc ceramic 1.5 KV
C19 - 0.1 mfd. tubular paper 600V
C20 - .22 mfd. tubular paper 200V
C21 - 7 mmfd. disc ceramic NPO
C22 - .002 mfd. disc ceramic 1.5KV
C23 - 2 mmfd. tubular
C24 - 140 mmfd. variable (PLATE)
C25 - 82 mmfd. disc ceramic 2.0KV
C26 - 680 mmfd. mica
C27 - Dual-525 mmfd. variable (LOAD)
C28 - .005 mfd. disc ceramic
C29 - .001 mfd. disc ceramic
C30 - .005 mfd. disc ceramic
C31 - 5.mfd. electrolytic 6V.
C32 - 8.mfd. electrolytic 450V.
C33 - 10.mfd. electrolytic 150V.
C34 - 8. mfd. electrolytic 450V.
C35 - .005 mfd. disc ceramic
C36 - .002 mfd. disc ceramic 1.5KV
C37 - .005 mfd. disc ceramic
C28, 39 - .001 mfd. disc ceramic from meter to chassis.
C40 thru 45 - .001 mfd. disc ceramic from filaments to chassis. C38 thru 45 not drawn to make drawing easier to read.
C46 - .005mfd. disc ceramic
C47 - 22mmfd. disc ceramic NPO

Resistors

in ohms. K=X1,000 M=X1,000,000

R 1 - 100K 1/2 watt
R 2 - 100 1/2 watt
R 3 - 15K 1 watt
R 4 - 39K 2 watt
R 5 - 47 1/2 watt
R 6 - 27 1/2 watt
R 7 - 1000 2 watt
R 8 - 100 1/2 watt
R 9 - 22K 1 watt
R10 - 100 1/2 watt
R11 - 3.9K 1 watt
R12 - 25K 4 watt Potentiometer (DRIVE)
R13 - 2.2K 1/2 watt
R14 - Meter shunt - special
R15 - 200 10 watts, wire wound
R16 - 5.6K 1 watt
R17 - Meter shunt - special
R18 - 47 1/2 watt
R19 - 3.9K 1 watt
R20 - 8.2K 2 watt
R21 - 39 2 watt
R22 - 10K 1/2 watt
R23 - 470K 1/2 watt
R24 - 470K 1/2 watt
R25 - 2.2K 1/2 watt
R26 - 500K potentiometer (AF GAIN)
R27 - 47K 1/2 watt
R28 - 4K 10 watt wire wound
R29 - 470K 1/2 watt
R30 - 330 1 watt
R31 - 47 1 watt
R32 - 5.6M 1/2 watt
R33 - 2.2K 1/2 watt

Switches

S1 - SPST Slide Switch Open on CRYSTAL, closed on VFO
S2 - DPDT Slide Switch Meter Selector
S3 - SPST on R26. Open on CW, closed on PHONE
S4 - Band selector switch, 3 sections. S4d is closed on 80M only. Switch is shown in 80M position.
S5 - SPST Slide Switch. Adds 680mmfd. to LOAD capacitor when needed on 80 and 40M only.

M1 - Meter 5 ma. movement, 10 and 200ma. scales.
Y1 - Crystal

MALFUNCTIONS AND PROBABLE CAUSES

In the event that your kit or wired transmitter does not operate properly, check your symptoms with the table below. Also check with the resistance and voltage charts above.

SYMPTOM	PROBABLE CAUSE
1) Transmitter will not operate when AC power is applied.	1-1. Defective 5 amp. fuse in PS-3. 1-2. Poor or incorrect contact in power plug or cable. 1-3. Defective switch in PS-3.
2) Fuse in Power Supply blows when AC power is applied.	2-1. Pin 3 of power plug at either end shorted to ground. 2-2. Pin 2 of power plug shorted to ground. 2-3. Shorted tube or tubes. 2-4. Shorted power cable.
3) Lack of Final Grid Current.	3-1. Defective 12BY7, 6BQ5 or 6883/6146. 3-2. Open meter. 3-3. Key contacts not closed. 3-4. Key line open. 3-5. Grid coil open. 3-6. Small rf chokes or coupling condenser in Oscillator or Buffer stage open. 3-7. R-17 open. 3-8. C-13 shorted.
4) Lack of Bias Voltage at Xtal Socket.	4-1. Defective crystal. 4-2. R-1 open. 4-3. Crystal socket not grounded. 4-4. Crystal socket shorted. 4-5. L-1 open.
5) Insufficient Drive or drooping drive.	5-1. Filament miswired on 12BY7 or 6BQ5. 5-2. Faulty 12BY7 or 6BQ5.
6) Final will not dip.	6-1. Check for malfunction 5 above. 6-2. Defective 6883/6146. 6-3. Incorrectly loaded pi-network. 6-4. Improper OSC-PLATE tuning and/or GRID tuning. 6-5. LOAD capacitor shorted. 6-6. LOAD open. 6-7. Knobs improperly installed, giving false readings. 6-8. Switch S-5 set incorrectly.
7) No reading on Plate Current meter.	7-1. Meter open. 7-2. R-15 open. 7-3. Open cable or connection to pin 3 of power plug. 7-4. Defective power supply - No high B+.
8) Antenna will not load properly.	8-1. Defective antenna system. 8-2. LOAD capacitor shorted (C-27). 8-3. C-25 or Switch S-4A shorted to ground. 8-4. Antenna dimensions improper. 8-5. Improper or open ground system.
9) No drop in Plate current when switching from CW to AM position	9-1. Defective 6AQ5-12AQ5. 9-2. Open or miswired filament on 6AQ5-12AQ5. 9-3. R-20 open. 9-4. S-3 (AF GAIN) open. 9-5. R-30 open.
10) No modulation.	10-1. See 9 above. 10-2. Open filament or miswired filament on 12AX7 or 6AQ5/12AQ5. 10-3. Open microphone cable. 10-4. Defective microphone. 10-5. Improper microphone (carbon microphone in set wired for Xtal microphone, or vice versa). 10-6. Improperly wired microphone plug. 10-7. C-29 open. 10-8. R-22 open. 10-9. AF GAIN control open or incorrectly set. 10-10. R-27 open. 10-11. R-29 open. 10-12. R-25 open. 10-13. Pin 8 of 12AX7 (V4) ungrounded.
11) Hum in modulation.	11-1. Unshielded microphone cable. 11-2. Open cable ground. 11-3. Tube shield left off V4.
12) Distortion, squeal or overmodulation.	12-1. A.F. Gain Control set too high. 12-2. Defective 12AX7A. 12-3. See 10 above. 12-4. Feedback from receiver. See section on Antenna Relay.
13) Unit smokes.	13-1. Disconnect transmitter from power supply and recheck resistance chart.
14) Arcing of Final Plate tuning or Antenna Load capacitors.	14-1. Insufficient loading. 14-2. Defective antenna system. 14-3. Bent plates on variable capacitors. 14-4. Open solder joint on Antenna Jack.